

アルミテック製アルミエルボ概略重量表

材質:A5052TD/O

有限会社 アルミテック

呼び径 (mm)	呼び厚 (mm)	厚さ (mm)	パイプ m重量(Kg)	90° ロングエルボ		90° ショートエルボ		45° ロングエルボ		45° ショートエルボ	
				軸長	概略重量(Kg)	軸長	概略重量(Kg)	軸長	概略重量(Kg)	軸長	概略重量(Kg)
15A 21.7 φ	S10S	2.1	0.347	59.82	0.027			29.91	0.013		
	S20S	2.5	0.404		0.027				0.013		
	S40	2.8	0.446		0.027				0.013		
	S80	3.7	0.561		0.034				0.017		
20A 27.2 φ	S10S	2.1	0.444	59.82	0.031			29.91	0.016		
	S20S	2.5	0.520		0.031				0.016		
	S40	2.9	0.593		0.035				0.018		
	S80	3.9	0.765		0.046				0.023		
25A 34.0 φ	S10S	2.8	0.736	59.82	0.047	39.88	0.031	29.91	0.023	19.94	0.016
	S20S	3.0	0.783		0.047		0.031		0.023		0.016
	S40	3.4	0.876		0.052		0.035		0.026		0.017
	S80	4.5	1.118		0.067		0.045		0.033		0.022
32A 42.7 φ	S10S	2.8	0.941	74.73	0.075	49.93	0.050	37.37	0.037	24.97	0.025
	S20S	3.0	1.003		0.075		0.050		0.037		0.025
	S40	3.6	1.185		0.089		0.059		0.044		0.030
	S80	4.9	1.560		0.117		0.078		0.058		0.039
40A 48.6 φ	S10S	2.8	1.080	89.80	0.103	59.82	0.069	44.90	0.052	29.91	0.034
	S20S	3.0	1.152		0.103		0.069		0.052		0.034
	S40	3.7	1.399		0.126		0.084		0.063		0.042
	S80	5.1	1.868		0.168		0.112		0.084		0.056
50A 60.5 φ	S10S	2.8	1.360	119.63	0.163	79.76	0.109	59.82	0.081	39.88	0.054
	S20S	3.5	1.680		0.201		0.134		0.100		0.067
	S40	3.9	1.859		0.222		0.148		0.111		0.074
	S80	5.5	2.547		0.305		0.203		0.152		0.102
65A 76.3 φ	S10S	3.0	1.852	149.62	0.277	99.70	0.185	74.81	0.139	49.85	0.092
	S20S	3.5	2.145		0.321		0.214		0.160		0.107
	S40	5.2	3.113		0.466		0.310		0.233		0.155
	S80	7.0	4.085		0.611		0.407		0.306		0.204
80A 89.1 φ	S10S	3.0	2.175	179.45	0.390	119.63	0.260	89.73	0.195	59.82	0.130
	S20S	4.0	2.866		0.514		0.343		0.257		0.171
	S40	5.5	3.872		0.695		0.463		0.347		0.232
	S80	7.6	5.215		0.936		0.624		0.468		0.312
90A 101.6 φ	S10S	3.0	2.491	209.44	0.688	139.57	0.348	104.72	0.344	69.79	0.174
	S20S	4.0	3.287		0.688		0.459		0.344		0.229
	S40	5.7	4.603		0.964		0.642		0.482		0.321
	S80	8.1	6.377		1.336		0.890		0.668		0.445
100A 114.3 φ	S10S	3.0	2.811	239.27	0.673	159.51	0.448	119.64	0.336	79.76	0.224
	S20S	4.0	3.715		0.889		0.593		0.444		0.296
	S40	6.0	5.471		1.309		0.873		0.655		0.436
	S80	8.6	7.654		1.831		1.221		0.916		0.610
125A 139.8 φ	S10S	3.4	3.905	299.09	1.697	199.39	1.132	149.55	0.849	99.70	0.566
	S20S	5.0	5.675		1.697		1.132		0.849		0.566
	S40	6.6	7.402		2.214		1.476		1.107		0.738
	S80	9.5	10.423		3.117		2.078		1.559		1.039
150A 165.2 φ	S10S	3.4	4.632	358.90	2.421	239.27	1.614	179.45	1.210	119.64	0.807
	S20S	5.0	6.744		2.421		1.614		1.210		0.807
	S40	7.1	9.452		3.392		2.261		1.696		1.131
	S80	11.0	14.282		5.126		3.417		2.563		1.709
200A 216.3 φ	S10S	4.0	7.150	478.54		319.02	2.281	239.27		159.51	1.141
	S20S	6.5	11.482								
	S40	8.2	14.368								
	S80	12.7	21.772								

■ 表示は製造範囲です。 ■ 表示のものは共通(S20S)の材料を使用して開先合わせにて対応しております。

同重量となります。

■ 表示は受注製作となります。

表の数値は材質A5052における計算値ですので実際の製品重量と異なる場合があります。予めご了承下さい。

※ グレー表示部の受注製作品は記載重量とは異なる場合がございます。